

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY


Land Office SLC

Lease No. 070835

Unit _____

ORIGINAL FORWARDED TO CASTER

SUNDRY NOTICES AND REPORTS ON WELLS



NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 18, 1954

Well No. 2 is located 1650 ft. from N line and 1650 ft. from E line of sec. 23

21 1/4 22 21 1/2 23 E
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Glenn Township (extension) Grand County Utah
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill a well to the Entrada sandstone for oil or gas production. Estimated maximum total depth is 1600 feet. Cable tools will be used, and all shows of oil or gas will be prudently tested. If oil or gas in commercial quantities is found above the Entrada the well will be completed at that point.

Approximately 60 feet of 3-5/8" 32.30# new O.D. casing will be run and cemented to the surface. Eight-inch hole will be drilled and 5 1/2" O.D. 14# new casing will be run and cemented if tests indicate commercial production.

(APPROVAL IS CONDITIONAL UPON COMPLIANCE WITH THE TERMS ATTACHED HERETO)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company WILLIAM D. HEWITT

Address 1636 Welton Street

Denver, Colorado

By George Down

Title Geologist

(SUBMIT IN TRIPLICATE)

Field Office **SLC**Lease No. **070825**Unit **RECEIVED****OCT 20 1954**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
ORIGINAL FOR FILED TO CASPER

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

Change of location & casing program ☒

(INDICATE ABOVE BY CHECKING AND SIGNATURE OF REPORT, NOTICE, OR OTHER DATA)

October 5, 1954

Well No. **2** is located **200** ft. from **N** line and **1190** ft. from **E** line of sec. **22****SW 1/4 Sec. 22**
(Sec. and Sec. No.)**23 S**
(Twp.)**23 E**
(Range)

(Meridian)

Glenn Area
(Field)**Grand**
(County or Subdivision)**Utah**
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

original location not drilled - Downs 10-29-54


We propose to drill a well to the Entrada sandstone for oil or gas production. Estimated maximum total depth is 1500 feet. Cable tools will be used, and all shows of oil or gas will be prudently tested. If oil or gas in commercial quantities is found above the Entrada the well will be completed at that point.

Approximately 60 feet of 10-5/8" O.D. casing will be run and cemented to the surface. Ten-inch hole will be drilled into the Morrison to accommodate an 8" cave string if necessary. 8 1/2" O.D. 14# new casing will be run and cemented if tests indicate commercial production.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **WILLIAM D. HEWITT**Address **1838 Welton Street****Denver, Colorado**Approved **10-29-54**By *George L. Down***Geologist**

Title _____



LOCATE WELL CORNERS

U. S. LAND OFFICE ----- **SLC**
SERIAL NUMBER ----- **070658**
LEASE OR PERMIT TO PROSPECT -----

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

DEC 6 - 1954

LOG OF OIL OR GAS WELL

Date Nov. 30, 1962

The summary on this page is for the condition of the well at above date

Commenced drilling October 12, 1964 1964 Finished drilling November 6, 1964

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 575 to 600 (u) No. 4, from 600 (u) to 625 (u)
 No. 2, from 625 (u) to 650 (u) No. 5, from 650 (u) to 675 (u)
 No. 3, from 675 (u) to 700 (u) No. 6, from 700 (u) to 725 (u)

IMPORTANT WATER SANDS

No. 1, from _____ to _____
 No. 2, from 777 to 888
 No. 3, from _____ to _____
 No. 4, from 1018 to 1128

CASING RECORD

Size casting	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
10 1/2	11 lb.	9	American Steel & Wire Co. Chicago, Ill.	1.76 ft.	Shoe A	Cut off at end of thread	From—	To—	Purpose
The block of lighter wire was in the form of a ring of wire, the location and shape of which is shown in the sketch. The wire was pulled from the block and the location of the wire was marked. The wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the wire was then cut into pieces of the length of the block and the									

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
10 5/8	60	25	Heavy belted rope		

PLUGS AND CAPTIONS

POOR COPY

MARK

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATE **1022**

Put to producing _____, 19____

The production for the first 24 hours was **Dr** barrels of fluid of which _____% was oil; _____% emulsion; _____% water; and _____% sediment. Gravity, °Bé. _____

Gas well cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. **72,000 CF**

40 EMPLOYEES

_____, Driller _____, Driller

R.R. James, Driller

John W. Moore (Contractor) _____, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	10	10	Surface sands and gravels
10	482	472	MANCOS SHALE - dark gray to black shale, silty streaks.
482	485	3	FERRON (?) Sandy member of Mancos, silty and sandy shale
485	564	79	(Mancos) Dark shale, slightly sandy, yellow near base
564	570	6	DAKOTA FORMATION. Black shale, some light, medium grained sandstone, coaly and bituminous fragments.
570	606	36	Gray and white, medium to fine grained sandstone, some black sh.
606	620	14	Gray, bentonitic, hard siltstone.
620	650	30	MERRISON FORMATION, Sandy Basin Member
650	650	0	Abrupt change to pale jade green bentonitic shale
650	650	0	Ditto, slightly sandy

(OVER)

FORMATION RECORD—Continued

POOR COPY

FORMATION RECORD—Continued

FROM	TO	TOTAL FEET	FORMATION
			MORRISON FORMATION 9 Continued)
660	675	15	Fine to medium grained, angular, poorly sorted pale green, slightly pyritic sandstone with white clay matrix.
675	703	28	White, tight, medium grained sandstone.
703	715	12	Reddish brown (some green) siltstone.
715	746	31	Deep purplish red shale and siltstone.
746	777	31	Sandstone, medium to fine grained, poorly sorted (water sand)
777	800	23	Green shale, bentonitic
800	820	20	Green and red shale (bedding?)
820	830	10	White sandstone (clay matrix)
830	835	5	Pale rose pink and pale green sandy siltstone.
835	840	5	Asky white sandstone
840	876	36	Green shale, some red shale
876	1012	136	Greenish gray, reddish, and some brown siltstone and bentonitic siltstone.
1012	1022	10	Morrison Formation, EAST WASH MEMBER
			Fine, white, medium grained, well sorted sandstone. (water)

T.D.


POOR COPY

SOUTH CISCO ANTICLINE - Grand County

22-218-235* NW NE NE, William D. Hewitt #2 (Salt Lake 070835),
Ref. #39

1954 STATUS: Dry 630' (U.C.R. 10-30-54)
OCT REMARKS: NEW DRILLING WELL. Spud 10-16-54.
*Corrected location.

1954 STATUS: Abd, TD 1122' (Co. 11-8-54)
NOV REMARKS: DRY HOLE OR FAILURE. 10" cc 60' w/25 sx.
Tops: Dakota 575', Morrison 612', Salt Wash 1012'.
Preparing to abandon.



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office SLC
Lease No. 070835
Unit _____

ORIGINAL FORWARDED TO OASPER

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED
DEC 6 - 1954

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Nov. 30, 1954

Well No. 2 is located 200 ft. from N line and 1120 ft. from E line of sec. 22

NE 1/4 NE 1/4 22
(1/4 Sec. and Sec. No.)

21S
(Twp.)

2SE
(Range)

S L
(Meridian)

South Cisco Anticline
(Field)

Grand
(County or Subdivision)

Utah
(State or Territory)

The elevation of the derrick floor above sea level is 4300 ft. approximately

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Well was drilled with cable tools to T.D. of 1022 in top of Salt Wash sandstone member of Morrison. Formation tops from samples were as follows: Dakota, 564; Morrison, 620; Morrison Salt Wash number 1012.

Hole size: 10" (surface to 3808); 8" (380 to 800'); 7" (800' to 1022, TD).

We propose to plug and abandon this hole, placing 10 sacks at TD to cover and protect Salt Wash; to mud back to 625 and bridge; to place 30 sacks cement between 625 and 850 to cover the Dakota section. We will mud back to 75' and place 60 sacks below and in surface pipe setting markers in cement at surface. Each plug is to be tested before proceeding to the next.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company William D. Hewitt

Address 1636 Nelson St.,

Denver, Colorado

Approved

DEC 1 - 1954

District Engineer


Orally approved 11-8-54 by H.C.S.

Not: Oral approval of this program was given (telephone) by Mr. Hewitt 11/6/54
JHD

By

George R. Damm

Title Geologist



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
ORIGINAL FORWARDED TO USGSPR

Land Office _____
Lease No. 070835
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	X
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Nov. 30, 19 54

Well No. 2 is located 200 ft. from N line and 1120 ft. from E line of sec. 22
~~NE 1/4~~ ~~NE 1/4~~ 22 21S 23E S.L.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
 South Cisco Anticline Grand Utah
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 4360 ft. approx

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well was plugged by placing 10 sacks cement at T.D. with dump bailer and then testing for shut off. Mudded back to 625, bridge set and 30 sacks cement placed with dump bailer. Plug tested and hole mudded back to 70'. Filled to surface with cement and erected marker.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company William D. Hewitt

Address 1836 Welton St.,

Denver, Colo.

JUN 17 1955

Approved

D. F. Small
District Engineer

By

George R. Downs
George R. Downs

Title

Geologist.

FEDERAL LAND

CONDITIONS OF APPROVAL

1. The lessee or operator shall mark the derrick or well in a conspicuous place with the name of the operator, well number, the land office and serial number of the lease, and location of the well and shall take all necessary precautions to preserve these markings.
2. A conductor or surface string of casing shall be run and cemented from bottom to surface unless other procedure is expressly authorized by this approval. The conductor or surface string shall be of sufficient weight and length and have installed thereon the proper and necessary high pressure fittings and equipment to keep the well under control in case an unexpected flow of gas, oil or water is encountered.
3. All showings of oil or gas are to be adequately tested for their commercial possibilities. All showings shall be properly protected by mud, cement, or casing so that each showing will be confined to its original stratum. Necessary precautions shall be taken to prevent waste or damage to other minerals drilled through and the U. S. Geological Survey, upon request, shall be furnished with carefully taken samples of such minerals as coal, potash and salt.
4. Lessee's Monthly Report of Operations (Form 9-329) shall be filed in duplicate with the office of U. S. Geological Survey, P. O. Box 400, Casper, Wyoming, not later than the sixth of the succeeding month. The report should show for this well any change of status occurring within the particular month such as date drilling commenced, suspended, resumed or completed, total depth as of the end of the month, and if shut down the reason therefor.
5. Two copies of the log of this well on Form 9-330, or other acceptable form and ~~when available~~ two copies of all electrical logs, directional, diameter and temperature surveys of the hole shall be filed with the district engineer within 15 days after such information is received by operator on completion of the well whichever is earlier.
6. The District Engineer, H.C.Scoville, 306 Federal Bldg., Salt Lake City 1, Utah Phone: 4-2552, Ext. 433, shall be notified on Form 9-331a in triplicate giving thereon all necessary details of the proposed operation or test for proper consideration and action sufficiently in advance of making casing or formation tests, shooting or acidizing, running or cementing casing, other than the surface or conductor string, to permit approval of the notice prior to date of proposed work.

Hewitt #2, SLC 070835

Approved SEP 13 1954

H.C.Scoville
District Engineer